

G/R-08/S6&R8

Fitting Instructions

Rolls Royce and Bentley Starters

Enclosed in the Starter Carton please find the new Gear Reduction Starter. This starter is a direct replacement to the original long heavy tube type Lucas Starter.

Check that your flywheel ring gear is sitting at 28mm from the centre of the starter locating dowel hole in to the front face of the Ring Gear.

Do not compare this measurement against the Original Lucas starter as our starters operate from the front of the ring gear not like the Lucas starter that comes forward from the rear of the Ring Gear.

We have found that some cars differ in the Mounting angle in the Saddle mount, which may cause our starter to interfere with other components. If this is the case our starter will require the cap screws to be undone and the starter rotated and marked where it is to be fitted. The two caps screws are @72mm Radius and Tapped at 6mm.

If this is require, the slot opening will also need modifying so that the ring gear will not interfere with sides of the slot opening.



G/R-08/S6&R8

<u>Warranty</u>

The manufacturer's warranty on all Hi-Torque gear reduction starter motors is for a period of (1) Year, covering the Starter Motor ONLY. The Warranty is subject to the following conditions.

Warranty Conditions

- All claims must be made in the warranty period of 12 Months.
- Any starter motor found to have faulty workmanship will be replaced free of charge.
- This warranty does not apply to items that have been subject to neglect, misuse, abuse, accidental
 or intentional damage, unauthorized repairs, modifications, incorrect application or installation.
 *Please check description below.
- The warranty does not cover the cost of freight, installation or removal of items.
- The warranty of 12 months only applies to items being used for normal road use.
- C.A.E. Performance Products recommend that this product be fitted by qualified personnel.

*<u>Starter motors that have been misused or abused include the following:</u> Water damage, Over heated, Pinion engaged while driving or hi revving and Extreme dust or corrosive conditions. It's up to the purchaser/ installer to ensure the starter motor is sealed or protected if used for Off Road or Marine applications.

ORDERING

Orders can be placed by phone, fax or e-mail. We prefer official purchase orders from account customers. Please quote the part number, quantity and any special requirements when ordering.

SHIPPING

All orders are dispatched upon payment (except account customers). We ship Australia-wide every day. If you wish to use your own courier, please advise us of your courier name & account details & we can organize pick-up Transport insurance can be arranged at the request of the purchaser.

RETURN OF GOODS

All part returned will incur a 20% re-stocking fee. Returns must be made within 30 Days. Freight is to be paid by customer unless the goods are being returned due to manufacturing defect or shipping error, in which case they are to be shipped using our Australia Post Reply Paid account. C.O.D. post will NOT be accepted under any circumstances. Goods specifically made to customer requests cannot be returned for credit. All goods remain the property C.A.E. Performance Products Pty Ltd until paid for in full.

DAMAGE

All goods are shipped in good condition & are packed accordingly. We can only handle damage claims for prepaid freight.

PAYMENT

Payment can be made by credit card, direct deposit, cheque/money order or cash over the counter. Please note that cheques & money orders must include the full amount of the order & freight costs. Personal cheques are subject to bank clearance (5 business days).

Filename: Rolls & Bentley 6 cyl Fitting Instructions Master.doc